



FROM THE MAKER



PROFFESIONAL POLYURETHANE FLOOR FINISH

OLD PRO
POLYURETHANE FLOOR FINISH

SPECIFICATIONS

VOC.	<350 g/L
Solids.	38%
Flash Point.	>100° F
Viscosity	150 - 250 cps
Solvents.	Mineral Spirits
Coverage	500 sq. ft/gal
Color	Clear



FEATURES

- Fortified with EZ Flow technology providing excellent flow & leveling
- Excellent scuff and scratch resistance
- Low odor, non-invasive smell
- Apply by roller, lambswool applicator, or T-bar
- Dries in about 6 – 8 hours, recoat after 8 – 12 hours (varies with conditions and air flow)
- Chemical resistant for Commercial and Residential use
- Clear finish with 1-year shelf-life, unopened container

PROFESSIONAL POLYURETHANE CLEAR FLOOR FINISH FOR ALL HARDWOODS

SAMPSON Coatings has been manufacturing commercial and industrial coatings since 1899. Professional coatings made from some of the finest resins, virgin solvents, and latest technologies in driers, our products stand the test of time for durability and chemical resistance. OLD PRO will provide many years of beauty and durability on all wood floor applications. OLD PRO applies easily, leaving a beautiful “like new” finish. Ideal for new installation, stained wood, screen and recoat jobs or natural wood.

SURFACE PREPARATION: New Wood or Newly Sanded Floors: Prepare the floor according to the NAWFA or NOFMA accepted manner. Remove dust completely by sweeping, vacuuming, and wiping the floor with a lint free cloth lightly dampened with mineral spirits. The floor, room and product temperature should be at least 65 degrees F.

AVAILABLE IN: GLOSS, SEMI-GLOSS, AND SATIN FINISHES in one- and five-gallon containers only.