

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 1 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

### SECTION 1: Identification

#### Product identifier

**Product name:** Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

**Product code:** GRMCG1D, GRMCG5D

#### Recommended use of the product and restriction on use

**Relevant identified uses:** Finishes, Coatings, and Related Materials

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

##### United States

Absolute Coatings  
1999 Elizabeth Street  
North Brunswick , New Jersey 089026316  
(732)821-3200

#### Emergency telephone number:

##### United States

CHEMTREC  
(703)527-3887 (24 HRS)  
(800)424-9300

### SECTION 2: Hazard(s) identification

#### GHS classification:

Skin irritation, category 2

Flammable liquids, category 3

Carcinogenicity, category 2

Reproductive toxicity, category 2

Specific target organ toxicity - single exposure, category 3, narcotic effects

Specific target organ toxicity - repeated exposure, category 2

#### Label elements

##### Hazard pictograms:



**Signal word:** Warning

#### Hazard statements:

H226 Flammable liquid and vapor

H315 Causes skin irritation

H351 Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H361 Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 2 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

H336 May cause drowsiness or dizziness

H373 May cause damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

### Precautionary statements:

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P271 Use only outdoors or in a well-ventilated area

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P302+P352 IF ON SKIN: Wash with plenty of water/ ...

P321 Specific treatment (see ... on this label)

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash it before reuse

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P370+P378 In case of fire: Use ... to extinguish

P308+P313 IF exposed or concerned: Get medical advice/attention

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P312 Call a POISON CENTER/doctor/.../if you feel unwell

P314 Get medical advice/attention if you feel unwell

P403+P235 Store in a well-ventilated place. Keep cool

P405 Store locked up

P403+P233 Store in a well-ventilated place. Keep container tightly closed

P501 Dispose of contents/container to...

**Hazards not otherwise classified:** None

### SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 108-65-6	1-Methoxy-2-propanol acetate	<6
CAS number: 1330-20-7	Xylene	<55
CAS number: 100-41-4	Ethyl Benzene	<10

**Additional Information:** None

### SECTION 4: First aid measures

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 3 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

### Description of first aid measures

#### General notes:

Show this Safety Data Sheet to the doctor in attendance.

#### After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

#### After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

#### After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

#### After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Skin contact may result in redness, pain, burning and inflammation.

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.

#### Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Suspected of causing cancer.

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

May cause damage to organs through prolonged or repeated exposure. Effects are dependent on exposure (dose, concentration, contact time).

### Immediate medical attention and special treatment

#### Specific treatment:

Overexposure via inhalation requires urgent medical treatment.

#### Notes for the doctor:

Treat symptomatically.

## SECTION 5: Firefighting measures

### Extinguishing media

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 4 of 13

### Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

#### **Suitable extinguishing media:**

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

#### **Unsuitable extinguishing media:**

Do not use water jet.

#### **Specific hazards during fire-fighting:**

Thermal decomposition may produce irritating/toxic fumes/gases.

Flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

#### **Special protective equipment for firefighters:**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

#### **Special precautions:**

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions.

Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

### SECTION 6: Accidental release measures

#### **Personal precautions, protective equipment and emergency procedures:**

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

#### **Environmental precautions:**

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

#### **Methods and material for containment and cleaning up:**

Do not touch damaged containers or spilled material unless wearing appropriate personal protective

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 5 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

### Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

### Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

## SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
WEEL	1-Methoxy-2-propanol acetate	108-65-6	TWA: 50 ppm
ACGIH	Xylene	1330-20-7	TWA: 100 ppm
	Xylene	1330-20-7	STEL: 150 ppm
OSHA	Xylene	1330-20-7	8-Hour TWA-PEL: 435 mg/m <sup>3</sup>
	Xylene	1330-20-7	8-Hour TWA-PEL: 100 ppm
	Xylene	1330-20-7	STEL: 150 ppm
	Xylene	1330-20-7	STEL: 655 mg/m <sup>3</sup>
	Ethyl Benzene	100-41-4	8-Hour TWA-PEL: 435 mg/m <sup>3</sup> (100 ppm)
NIOSH	Xylene	1330-20-7	REL-TWA: 435 mg/m <sup>3</sup>

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 6 of 13

<b>Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC</b>
--

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Xylene	1330-20-7	REL-TWA: 100 ppm
	Xylene	1330-20-7	STEL: 655 mg/m <sup>3</sup>
	Xylene	1330-20-7	STEL: 150 ppm
	Ethyl Benzene	100-41-4	REL-TWA: 435 mg/m <sup>3</sup> (100 ppm [10-hr])
	Ethyl Benzene	100-41-4	STEL: 545 mg/m <sup>3</sup> (125 ppm)
	Ethyl Benzene	100-41-4	IDLH: 800 ppm
United States(California)	Xylene	1330-20-7	8-Hour TWA-PEL: 100 ppm
	Xylene	1330-20-7	PEL-STEL: 150 ppm (15- minute)
	Xylene	1330-20-7	PEL Ceiling: 300 ppm
	Ethyl Benzene	100-41-4	8-Hour TWA-PEL: 22 mg/m <sup>3</sup> (5 ppm)
	Ethyl Benzene	100-41-4	PEL-STEL: 130 mg/m <sup>3</sup> (30 ppm)
	1-Methoxy-2-propanol acetate	108-65-6	15-Minute STEL: 811 mg/m <sup>3</sup> (150 ppm)
	1-Methoxy-2-propanol acetate	108-65-6	8-Hour TWA-PEL: 541 mg/m <sup>3</sup> (100 ppm)

### Biological limit values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
United States	Xylene	1330-20-7	Methylhippuric acids		End of shift	1.5 g/g

### Information on monitoring procedures:

Not determined or not applicable.

### Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

### Personal protection equipment

#### Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

#### Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 7 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

### General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Clear liquid
Odor	Solvent
Odor threshold	N/A
pH	N/A
Melting point/freezing point	N/A
Initial boiling point/range	136.1° C
Flash point (closed cup)	28.3° C
Evaporation rate	Slower than diethyl ether
Flammability (solid, gas)	N/A
Upper flammability/explosive limit	N/A
Lower flammability/explosive limit	N/A
Vapor pressure	10.95 hPa estimated
Vapor density	Heavier than air
Density	0.96 g/cc
Relative density	N/A
Solubilities	Not soluble in water. Reacts with water to liberate carbon dioxide gas.
Partition coefficient (n-octanol/water)	N/A
Auto/Self-ignition temperature	432.22° C
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

### Other information

## SECTION 10: Stability and reactivity

### Reactivity:

Not reactive under recommended handling and storage conditions.

### Chemical stability:

Stable under recommended handling and storage conditions.

### Possibility of hazardous reactions:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 8 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

### Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

### Incompatible materials:

None known.

### Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
1-Methoxy-2-propanol acetate	oral	LD50 Rat: 5155 mg/kg
	dermal	LD50 Rabbit: >5000 mg/kg
Xylene	dermal	LD50 Rabbit: 1700 mg/kg
	inhalation	LC50 Rat: 5000 ppmV (4 h)
	oral	LD50 Mouse: 5251 mg/kg
Ethyl Benzene	inhalation	LC50 Rat: 4000 ppmV (4 h)
	oral	LD50 Rat: 5460 mg/kg
	dermal	LD50 Rabbit: 17,800 mg/kg

### Skin corrosion/irritation

#### Assessment:

Causes skin irritation.

#### Product data:

No data available.

#### Substance data:

Name	Result
Xylene	Causes skin irritation.

### Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Respiratory or skin sensitization

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Carcinogenicity

#### Assessment:



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 9 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

Suspected of causing cancer.

**Product data:** No data available.

**Substance data:** No data available.

### International Agency for Research on Cancer (IARC):

Name	Classification
Xylene	Group 3
Ethyl Benzene	Group 2B
1-Methoxy-2-propanol acetate	Not Applicable

### National Toxicology Program (NTP):

Name	Classification
Xylene	Not Applicable
Ethyl Benzene	Not Applicable
1-Methoxy-2-propanol acetate	Not Applicable

**OSHA Carcinogens:** Not applicable

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:**

Suspected of damaging fertility or the unborn child.

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:**

May cause drowsiness or dizziness.

**Product data:**

No data available.

**Substance data:**

Name	Result
1-Methoxy-2-propanol acetate	May cause dizziness or drowsiness.

### Specific target organ toxicity (repeated exposure)

**Assessment:**

May cause damage to organs through prolonged or repeated exposure.

**Product data:**

No data available.

**Substance data:**

Name	Result
Ethyl Benzene	May cause damage to hearing organs through prolonged or repeated exposure.

### Aspiration toxicity

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 10 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Ethyl Benzene	May be fatal if swallowed and enters airways.

**Information on likely routes of exposure:**

No data available.

**Symptoms related to the physical, chemical and toxicological characteristics:**

No data available.

**Other information:**

No data available.

## SECTION 12: Ecological information

**Acute (short-term) toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
1-Methoxy-2-propanol acetate	LC50 Pimephales promelas: 130 mg/L (96 hours)

**Chronic (long-term) toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
1-Methoxy-2-propanol acetate	NOEC Oryzias latipes: 47.5 mg/L (14 days)

**Persistence and degradability**

**Product data:** No data available.

**Substance data:**

Name	Result
1-Methoxy-2-propanol acetate	Readily biodegradable.
Xylene	Readily biodegradable in water.

**Bioaccumulative potential**

**Product data:** No data available.

**Substance data:**

Name	Result
1-Methoxy-2-propanol acetate	Log Kow: 1.2
Xylene	BCF: >8.1 - <25.9

**Mobility in soil**

**Product data:** No data available.

**Substance data:**

Name	Result
Xylene	Moderately Mobile (Log Koc: 2.73)

**Results of PBT and vPvB assessment**

**Product data:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 11 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT..

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB..

### Substance data:

#### PBT assessment:

1-Methoxy-2-propanol acetate	Substance is not PBT.
------------------------------	-----------------------

#### vPvB assessment:

1-Methoxy-2-propanol acetate	Substance is not vPvB.
------------------------------	------------------------

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:


Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

### Contaminated packages:


Not determined or not applicable.

## SECTION 14: Transport information


### United States Transportation of dangerous goods (49 CFR DOT)

UN number	UN1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None

### International Maritime Dangerous Goods (IMDG)

UN number	UN1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 12 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

Packing group	III
Environmental hazards	None
Special precautions for user	None

### SECTION 15: Regulatory information

#### United States regulations

##### Inventory listing (TSCA):

108-65-6	1-Methoxy-2-propanol acetate	Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

**Export notification under TSCA Section 12(b):** None of the ingredients are listed.

**SARA Section 302 extremely hazardous substances:** None of the ingredients are listed.

##### SARA Section 313 toxic chemicals:

108-65-6	1-Methoxy-2-propanol acetate	Not Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

##### CERCLA:

1330-20-7	Xylene	Listed	100 lb
100-41-4	Ethyl Benzene	Listed	1000

##### RCRA:

1330-20-7	Xylene	Listed	U239
100-41-4	Ethyl Benzene	Listed	F003

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

##### Massachusetts Right to Know:

108-65-6	1-Methoxy-2-propanol acetate	Not Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

##### New Jersey Right to Know:

108-65-6	1-Methoxy-2-propanol acetate	Not Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

##### New York Right to Know:

108-65-6	1-Methoxy-2-propanol acetate	Not Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

##### Pennsylvania Right to Know:

108-65-6	1-Methoxy-2-propanol acetate	Not Listed
----------	------------------------------	------------

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.13.2020

Page 13 of 13

## Classic World Moisture Cure Crystal Clear Finish Super High Gloss 450 VOC

1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

### California Proposition 65:

**⚠️WARNING:** This product can expose you to Ethyl Benzene; which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Absolute Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Absolute Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

**NFPA:** 2-3-0

**HMIS:** 3\*-3-0

**Initial preparation date:** 05.13.2020

### Revision Notes:

Revision Date	Notes
2020-04-30	Version 02

**End of Safety Data Sheet**