



# CLASSIC WORLD SEAL KOTE UNIVERSAL HARDWOOD SANDING SEALER

## OVERVIEW: Very Fast Drying Universal Sanding Sealer For All Hardwood Flooring Applications

Sampson Seal Kote Universal Sealer is a shellac-based sealer that doesn't raise the grain and can be top-coated with any polyurethane. The fast-drying sealer is easily applied, VOC compliant and seals in old stains and odors. This ready-to-use universal sealer can be applied over new wood or existing finishes.

### PHYSICAL CHARACTERISTICS

- Sheens: ..... N/A
- Color: ..... Amber
- Solids: ..... 14 - 16%
- VOC Content: ..... 730 VOC
- Odor: ..... Alcohol Like
- Gloss Level (60%): ..... N/A
- Stability: ..... 18 Months
- Packaging Size: ..... 5 Gallon & 1 Gallon

### APPLICATION CHARACTERISTICS

- Dry Color Clarity: ..... Amber Clear
- Coverage Rate: ..... 600 sq. ft. (Varies with surface porosity)
- Dry Time: ..... 1 Hour
- Fully Cured: ..... 7 - 10 Days
- Leveling: ..... Very Good
- Defoaming: ..... Excellent
- Working Temp: ..... Room Temperature  
65 - 75° F
- Application Methods: ..... T-Bar Applicator,  
Brush, or Roller
- Storage Temp: ..... Between 50 - 70° F
- Professional Market: ..... Commercial

### FEATURES

- Universal Sealer - Shellac-Based
- Fast Drying - Clear Color
- Can Be Topcoated With Any Polyurethane
- Easily Applied - VOC Compliant
- Seals Out Old Stains And Odors

### BENEFITS

- Ready To Use, Easy To Apply
- Dries In 1 Hour
- Will Not Raise Grain
- Apply Over New Wood Or Existing Finishes
- Apply With T-Bar Applicator, Brush, Or Roller

**sampsoncoatings.com**  
 info@sampsoncoatings.com  
 800-368-2677  
 1999 Elizabeth St.  
 North Brunswick, NJ 08902

MADE IN THE U.S.A.

