



CRAFTSMAN'S CHOICE POLYURETHANE PROFESSIONAL FLOOR FINISH

OVERVIEW: Proven Quality & Value with Consistent Results

Sampson Craftsman's Choice Professional Floor Finish is an extremely durable clear coating recommended for interior residential or commercial floors, paneling, cabinets, doors, trim and furniture.

PHYSICAL CHARACTERISTICS

Sheens: Gloss, Semi Gloss, Satin & Dull Rub

Color: Amber

Solids: 38 - 42%

VOC Content: 550 VOC

Odor: Solvent Like

Gloss Level (60%): Minimum 90 GU for Gloss
 60 - 65 GU for Semi Gloss
 38 - 43 GU for Satin
 20 - 24 GU for Matte

Stability: 18 Months

Packaging Size: 5 Gallon & 1 Gallon

APPLICATION CHARACTERISTICS

Dry Color Clarity: Amber Clear

Coverage Rate: 500 sq. ft. (Varies with surface porosity)

Dry Time: 3 - 4 Hours

Fully Cured: 7 - 8 Days

Leveling: Very Good

Defoaming: Excellent

Working Temp: Room Temperature
 65 - 75° F

Application Methods: T-Bar Applicator, Brush, or Roller

Storage Temp: Between 50 - 78° F

Professional Market: Commercial & Residential Use

FEATURES

- Durable Film Build
- Excellent Flow and Leveling
- Abrasion & Scuff Resistant

BENEFITS

- Abrasion & Scuff Resistant
- Durable Film Build
- Excellent Flow and Leveling
- Available in 550 VOC Formulation



1999 Elizabeth Street • North Brunswick, NJ 08902
 OFFICE (732) 821-3200 | FAX (732) 821-8180
CANLAKCOATINGS.COM