



# SAMSEAL PROFESSIONAL POLYURETHANE

## OVERVIEW: Durable Quick Recoat Sealer

Sampson Sam Seal Professional Urethane Wood Finish is an extreme durable sealer formulated to seal and protect bare wood surfaces. It is for interior residential or commercial floors, paneling, cabinets, doors, trim, bar tops and furniture, etc. It is superior to conventional urethanes in toughness, resistance to alcohol, water, cleaners and abrasion.

### PHYSICAL CHARACTERISTICS

- Sheens: ..... Gloss, Semi Gloss & Satin
- Color: ..... Amber
- Solids: ..... 38 - 42%
- VOC Content: ..... 550 VOC
- Odor: ..... Solvent Like
- Gloss Level (60%): ..... Minimum 90 GU for Gloss  
 ..... 60 - 65 GU for Semi Gloss  
 ..... 38 - 43 GU for Satin  
 ..... 20 - 24 GU for Matte
- Stability: ..... 18 Months
- Packaging Size: ..... 5 Gallon, 1 Gallon & Quart

### APPLICATION CHARACTERISTICS

- Dry Color Clarity: ..... Amber Clear
- Coverage Rate: ..... 500 sq. ft. (Varies with surface porosity)
- Dry Time: ..... 3 - 4 Hours
- Fully Cured: ..... 7 - 8 Days
- Leveling: ..... Very Good
- Defoaming: ..... Excellent
- Working Temp: ..... Room Temperature  
 65 - 75° F
- Application Methods: ..... T-Bar Applicator, Brush, or Roller
- Storage Temp: ..... Between 50 - 78° F
- Professional Market: ..... Commercial & Residential Use

### FEATURES

- High Build
- Quick Recoat
- Low Odor Formula
- Alkyd Free

### BENEFITS

- Seals and Protects
- Sands Easily
- Superior Abrasion Resistance
- Exceptional Flow and Leveling



1999 Elizabeth Street • North Brunswick, NJ 08902  
 OFFICE (732) 821-3200 | FAX (732) 821-8180  
**CANLAKCOATINGS.COM**