



CLASSIC WORLD SEAL KOTE UNIVERSAL HARDWOOD SANDING SEALER

OVERVIEW: Very Fast Drying Universal Sanding Sealer For All Hardwood Flooring Applications

Sampson Seal Kote Universal Sealer is a shellac-based sealer that doesn't raise the grain and can be top-coated with any polyurethane. The fast-drying sealer is easily applied, VOC compliant and seals in old stains and odors. This ready-to-use universal sealer can be applied over new wood or existing finishes.

PHYSICAL CHARACTERISTICS

- Sheens: N/A
- Color: Amber
- Solids: 14 - 16%
- VOC Content: 730 VOC
- Odor: Alcohol Like
- Gloss Level (60%): N/A
- Stability: 18 Months
- Packaging Size: 5 Gallon & 1 Gallon

APPLICATION CHARACTERISTICS

- Dry Color Clarity: Amber Clear
- Coverage Rate: 600 sq. ft. (Varies with surface porosity)
- Dry Time: 1 Hour
- Fully Cured: 7 - 10 Days
- Leveling: Very Good
- Defoaming: Excellent
- Working Temp: Room Temperature
65 - 75° F
- Application Methods: T-Bar Applicator, Brush, or Roller
- Storage Temp: Between 50 - 70° F
- Professional Market: Commercial

FEATURES

- Universal Sealer - Shellac-Based
- Fast Drying - Clear Color
- Can Be Topcoated With Any Polyurethane
- Easily Applied - VOC Compliant
- Seals Out Old Stains And Odors

BENEFITS

- Ready To Use, Easy To Apply
- Dries In 1 Hour
- Will Not Raise Grain
- Apply Over New Wood Or Existing Finishes
- Apply With T-Bar Applicator, Brush, Or Roller



1999 Elizabeth Street • North Brunswick, NJ 08902
 OFFICE (732) 821-3200 | FAX (732) 821-8180
CANLAKCOATINGS.COM